



OPTIONS

Methods of installation

attached by bolts to foundation

Ashtray

• include

Container


galvanized steel container

DESCRIPTION

The Simple litter bin is one of the most popular small architecture products. Its minimalist form fits perfectly into modern urban arrangements, as well as not disturbing the classic character of historic districts.

The 03.061.1 version of the bin is characterised by a top with a built-in ashtray.

The bin is available in two variants: - Entirely made of stainless steel - With a construction made of painted carbon steel with a stainless steel container



GENERAL TECHNICAL DATA

Weight

- 57 kg

Dimensions

- width: 30 cm - height: 100 cm - depth: 30 cm

Capacity

- bin capacity: 30 l

- capacity of ashtray: 2 l

Materials

- construction - stainless steel or carbon steel

- container - stainless steel

- insert - galvanised sheet metal

ZANO



Product:
Litter bin with ashtray Simple
Catalog number: 03.061.1
Designer:

Mateusz Wełmiński

In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Offcial Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright , Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Mirosław Zarotinski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Mirosław Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.

NOTE: The drawings do not reflect the actual dimensions of the foundation. They are only exemplary assembly schemes taking into account the type of anchoring and the substrate material to which the furniture is to be fixed.

The size of the foundation depends on the local foundation conditions.









INSTALLATION INTO PAVING WITH FOUNDATION

Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- 3. Stone paving / concrete paving / stone slabs / concrete slabs
- 4. Sand ballast (approx. 2 4 cm)
- 5. Stone aggregate substructure
- Concrete foundation, class C16/20 (top surface concrete 10 cm below paving surface)
- **7.** Ground

INSTALLATION TO PAVING

Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- 3. Stone paving / concrete paving / stone slabs / concrete slabs
- **4.** Sand ballast (approx. 2 4 cm)
- 5. Stone aggregate substructure
- 6. Ground

CONCRETE / ASPHALT MOUNTING

Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- **3.** Fixed hardened surface e.g. concrete or asphalt
- Concrete foundation, class C16/20 (top surface concrete 10 cm below paving surface)
- **5.** Stone aggregate substructure
- 6. Sand ballast (approx. 2 4 cm)
- **7.** Ground

MOUNTING TO CONCRETE FOUNDATION

Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- 3. Concrete foundation, class C16/20 (top surface concrete 10 cm below paving surface)
- 4. Ground